Belinea

[Belinea 10 15 55]

Elegant Office Display for an excellent price

With the latest generation of the Belinea 10 15 55 every user can very easily modernize his office.

The elegant design is as persuasive as the high quality and the favourable price. A good picture performance, e.g. for text applications and searching in the Internet, as well as the integrated speakers make this 15 inch TFT display a reliable partner in every office area. Certifications like TCO99 and TÜV Ergonomie as well as the option to work with a VESA-compliant swivel arm or wall mounting show that ergonomic working with this Belinea 10 15 55 goes without saying.



SilverBlackStyle

Integrated speaker for multimedia applications

D-Sub connection for analogue graphic cards

Belinea 10 15 55 – Elegance for every office

- 15 inch (38,1 cm)
- analogue
- Sound, TN-Panel
- Viewing angle: 130° / 110°
- Response time rise / fall: 12 / 18 ms

Target Groups

- **Small and medium business**
- **Price sensitive user**
- **Representative design**

MAXDATA Computer GmbH & Co. KG • Elbestraße 12-16 • D-45768 Marl • www.maxdata.de

05/2004 ® Errors and omissions exempt.

MAXDATA
REAL HARD WARE

Belinea 10 15 55 – Technical Data

Panel characteristics

Image size	15“
Viewable image size in inch / cm	15“ / 38.1
Max. picture size (w x h) in mm	304,1 x 228.1
Physical resolution	1024 x 768
Pixel pitch in mm	0.297 x 0.297
Active Matrix TFT	•
Displayable colours (max.)	TN / CPT
Brightness in cd / qm	16.2 Mio (Dither)
Contrast ratio	250
Viewing angle horizontal	400:1
Viewing angle vertical	130°
Responsetime: rise / fall in ms	110°
Coating	12 / 18
Panel technology / manufacturer	TN / HannStar
Backlight	2 CCFLs

Electronic data

Horizontal frequency in kHz	31 - 61
Vertical frequency in Hz	56 - 75
Bandwidth in MHz	80
Input voltage 110-230V, 50-60 Hz	•
Power consumption in Watt (On / Sleep)	40 / 1
Input signal (VGA-card) analog / digital	• / –
Output audio amplifier	2 x 1 Watt

Features

Factory / user defined modes	12 / 9
OSD	•
Integrated microphone	–
Integrated speaker	•
Power supply in the panel /in the stand / external	• / – / –
Tilt back / forth	20° / 5°
Swivel right / left	– / –

Controls

Brightness / contrast	• / •
H / V position	• / •
Automatic picture-adjustment / colour calibration	external / •
Temperatur	•
Fine adjustment horizontal (clock) / vertical (phase)	• / •
Display at lower resolutions: 1:1 / full screen	– / •
Zoom / frequency	– / •
Recall / video signal selection	• / –
OSD position / OSD language(s)	• / 5
Mute	external
Volume	external

Max. refresh rates in Hz with resolution

640 x 480	75
800 x 600	75
1024 x 768	75
1152 x 864	–
1280 x 1024	–

Approvals / Standards

Plug & Play, DDC1 / 2B	•
Power-Management:	
Energy Star / Energy Label	• / •
TCO99	•
TÜV GS /TÜV Ergonomie	• / •
DIN 29241 / ISO 9241-3, -7, -8 / ISO 13406-2	• / • / •
Compliant to mountings acc. to VESA standard	• (75 x 75 mm)
MAC compliant	•

Connections

15-pin Mini-D-Sub	•
24-pin DVI-D	–
Headphone plug	–
Audio In	•

Accessories

User manual (languages)	10
Power cable	•
Video connect.15-pin Mini-D-Sub	• (non detachable)
Video connect. 24-pin DVI-D	–
Audio cable	•
Microphone cable	–

Physical specification

Size (w x h x d) in mm	340 x 354 x 162
Net / gross weight in kg	2.8 / 3.8

Warranty

3 years incl. Panel and Backlight	•

Austria
MAXDATA Computer GmbH
Ignaz-Köck-Straße 9 • 1210 Wien

Benelux
MAXDATA Benelux B.V.
Bredaseweg 113-115 • 4872 LA Etten-Leur

España • Portugal
MAXDATA Iberia
Edificio Prisma • C/ Colquide, 6
28230 – Las Rozas (Madrid)

France
MAXDATA S.A.R.L.
1, rue de Gevaudan • SILIC 1726
91017 EVRY-LISSES

Germany
MAXDATA Computer GmbH & Co. KG
Elbestraße 12-16 • 45768 Marl

Italy
MAXDATA Italia S.r.l.
Strada 1 • Palazzo F1
I-20090 Milanofiori, Assago (MI)

Poland
MAXDATA Sp. z o.o.
Ursynów Business Park • Ul. Puławska 303
02-785 Warszawa

Switzerland
MAXDATA Computer AG
Haldenstrasse 5 • 6340 Baar

United Kingdom
MAXDATA UK Limited
The MAXDATA Centre • Downmill Road
Bracknell, Berkshire RG12 1QS

With compliments: